



e700

AUTOMATIC TRANSPORT
VENTILATOR

MULTIPLE MODES, COMPACT, LIGHTWEIGHT, EASY TO USE

The e700 ventilator ushers in a “new era” in controlled ventilation for resuscitation and patient transport!

These electronically controlled, pneumatically powered ventilators provide a range of ventilation solutions for all types of patient requirements and all levels of pre-hospital and in-hospital healthcare professionals.

LONG LASTING
BATTERY
18h - 24h

ECONOMICAL
Low gas consumption

LIGHTWEIGHT
2.4 kg / 5.29 lbs



SIMPLICITY

The ventilation solutions offered by the e700 cannot be compared to any other products of its type. The units are self-contained and only require attachment to a regulated oxygen supply and a transport ventilator circuit for immediate use. The easily replaceable, long lasting (18h - 24h) battery can be charged while inside the ventilator or can be removed for charging and quickly replaced by a fresh battery pack. The display lighting has adjustable brightness for easy visualization of the ventilator settings in any ambient light conditions. Designed for a range of patient sizes (from large adult to infant), the e700 comes in a very small and lightweight package.

SAFETY

The continuous monitoring of ventilation parameters ensures that the device is always fully functional and ready for immediate use. The wide range of both visual and audible alarms provides the healthcare professional with warnings of any changes in patient or device parameters. Correction of any alarm is simple to achieve due to the compact and easy to operate control layout. The Intuitive Patient Apnea Backup (IPAB) mode provides additional security for the spontaneously breathing patient on CPAP by automatically commencing ventilations should their inspiratory efforts cease.

FUNCTIONALITY

The simplicity of operation masks the level of sophistication offered by the e700, providing ventilation for both resuscitation and transport with the minimum of control adjustments required for simple patient set up. The range of ventilation modes offered provides “ICU level” patient care while maintaining the ease of operation for all patient care and transport situations in the pre-hospital and in-hospital setting. The inclusion of ventilation modes for “mask or protected airway CPR”, with visual and audible prompts, adds another dimension to the application for these products not found on other ventilators.

CONTROLLABILITY

The operation of the controls of the e700 provide an ease of use concept that is second to none. These products are designed to speed up and simplify even the most complex ventilation set up. There are no multiple screens to scroll through to establish patient ventilation parameters. The units have an initial, pre-set, start-up mode requiring only the selection of patient size to begin ventilation.

ECONOMY

In addition to the patient care benefits, the e700 ventilator provides excellent low gas consumption and an extremely long battery operating time. This assists in providing controlled ventilation to the patient over an extended period, making the e700 ventilator ideal for long transports where both electrical and oxygen supplies are always a critical concern.

SPECIFICATIONS

DEVICE CLASS PER MDD	II b	
CLASSIFICATION PER IEC60601-1	Protection against electric shock	Class II
	Protection against electric shock	Type BF
	Protection against water	IP X4
POWER SOURCE	Compressed Oxygen, 45 to 87 PSI (3-6 Bar)	
CIRCUIT CONTROL SOURCE	Electric	
VENTILATION MODES	A/C (VCV,PCV), SIMV w/ PSV, BiLVL w/ PSV, CPAP w/ PSV, Mask CPR and Intubated CPR	
SUPPORTING VENTILATION	PSV: 0, 4-35 cmH ₂ O (± 10% or ± 2 cmH ₂ O)	
VENTILATION RATE	5 - 60 (± 10% or ± 1BPM)	
MINUTE VOLUME (L)	Calculated	
TIDAL VOLUME (ML)	50 - 2000 ± (4ml + 15%) BTPS *	
TIDAL VOLUME IN CPR MODE (ML)	50 - 1400 ± (4ml + 15%) BTPS *	
MAXIMUM DELIVERED FLOW (L/MIN)	100 - 120	
MANUALLY TRIGGERED VENTILATION	Yes, set flow rate or pressure will be delivered during I time then Inspiratory hold	
MAXIMUM INSPIRATORY HOLD TIME	6 sec.	
I:E RATIO	1:4 - 3:1 (± 20%)	
PEEP (CM H2O)	0,4-20 (± 10% or ± 2 cmH ₂ O)	
PSV	OFF, 4 - 35 (± 10% or ± 2 cmH ₂ O)	
CPAP (CM H2O)	4-20 (± 10% or ± 2 cmH ₂ O)	
O2 (%)	60 or 100 (± 15%)	
PMAX (CM H2O)	10 - 80 (± 10% or ± 2 cmH ₂ O)	
PMIN (CM H2O)	0 - 20 (± 10% or ± 2 cmH ₂ O)	
PCV (CM H2O)	4-50 (± 10% or ± 2 cmH ₂ O)	
TI (SEC.)	0.2 - 9 (± 20%)	
TRIGGER SENSITIVITY (L/MIN)	1 -15, or 2 cmH ₂ O below baseline in CPAP mode only	
INHALATION PRESSURE (CM H2O)	4-50 (± 10% or ± 2 cmH ₂ O)	
PRESSURE VENTILATION TERMINATION	20% - 80% of max. Flow	
APNEA BACK UP TIME (SEC.)	10-60 (± 0.5s)	
BATTERY OPERATING TIME AT ROOM TEMPERATURE (HRS.)	> 18 hrs for default settings (Data obtained using fully charged new battery)	
ALTITUDE COMPENSATION	up to 4000m (13000 feet)	
BATTERY HOT SWAP	No	
BUILT-IN BATTERY CHARGER	Yes	
AC/DC POWER SUPPLY	100-240 VAC/ 19 VDC, 4.74 A	
PATIENT CIRCUIT	O-Two Electronic Ventilator Circuit	
MOUNTING BRACKET	Mounting brackets for road ambulance and mobile setting	
DISPLAY	4.3" Color TFT	
LIVE MONITORING	Mve,Vte,Paw(AV),PAW(Peak), Rate (bpm), Battery level	
REAL TIME WAVEFORM	Pressure or Flow	
DAY/NIGHT DISPLAY MODE	Yes	
PARAMETER SETTINGS	Control Selection Knob	
LOCK KEY FUNCTION	Yes	
PAUSE FUNCTION	Yes	
NOISE LEVEL IN NORMAL USE	Less than 65 dBA	

ALARMS (VISUAL AND AUDIBLE)	Gas Supply Pressure, Airway Pressure limits, Minute Volume limits, Battery status, APNEA, Breathing Circuit Integrity, Leakage and Blockage		
AUDIBLE SILENCE	Yes, 120 second max		
DIMENSIONS (MM)	250 x 200 x 155		
WEIGHT (KG/LBS) WITH/WITHOUT BATTERY	2.4/1.77 5.29/3.9		
INTERNAL VOLUME OF THE COMPLETE RESPIRATORY SYSTEM (REUSABLE AND DISPOSABLE)	approx. 690 ml without mask approx. 800 ml with mask		
DEAD SPACE OF PATIENT VALVE WITH ELBOW	Approx. 35 ml		
COMPLIANCE (DISPOSABLE) HOSE SYSTEM	16.6 ml/kPa		
RESISTANCE OF PATIENT HOSE SYSTEM (INHALATION AND EXHALATION):	Less than 6 cmH ₂ O at 60 l/min & Less than 6 cmH ₂ O at 30 l/min		
ENVIRONMENT CONDITION	Ventilator	Operating	- 18°C to +50°C, Rh: 15% to 95%
		Storage	- 40°C to +60°C, Rh: 15% to 95%
	Battery Pack	Charge	0°C to +40°C
		Discharge	- 20°C to +60°C
	Patient Circuit	Storage	- 20°C to +35°C, low humidity and no corrosive gas atmosphere.
		Operating	- 18°C to +50°C, Rh: 15% to 95%
	Storage	- 20°C to +60°C, Rh: 15% to 95%	

* BTPS: Volume measurements corrected to Body temperature 37°C and Barometric pressure 101.3Kpa under saturated conditions (100% Humidity). Note: Measurement uncertainty: 5% for volume parameters and 6% for pressure parameters.

ORDERING INFORMATION

01EVE700	e700 - Electronic Automatic Transport Ventilator c/w Disposable Patient Circuit, Resuscitation Mask, 6 Foot Supply Hose*, Calibrated Test Lung and Power Supply (Specify Country of Use)	Each
01CV8030-CS	O-Two Medical Single-Use Electronic Transport Ventilator 6 Foot Circuit with Protective Sleeve. For e500, e600 and e700	Case/10
01CV7035	O-Two Medical "e" Series Ventilator "Smart Mount" Multi-configuration Mounting Bracket (Ambulance Cot, Hospital Stretcher, Bed, Roll Stand)	Each
01CV8040-CS	O-Two Medical "e" Series Ventilator Replacement Intake Filter/Cover	Case/10
01TA1852	O-Two Medical "e" Series Ventilator Replacement 1 Litre Test Lung with Compliance Restrictor	Each
01FV4303-DISS	O-Two 6 Foot (1.85 Meter) O2 Supply Hose with 9/16 DISS Nut and 9/16" DISS Nut Ventilator Connection	Each
01CV9100	O-Two Medical "e" Series Replacement Lithium Ion Replacement Battery	Each
01CV0105	Power Supply - eSeries	Each
01CV0106	Power supply cord for eSeries power supply	Each
01CV0102-EU	Power supply cord for eSeries power supply	Each
01CV7050	eSeries Automatic Transport Ventilator Carrying Case - With sling-style shoulder strap (specifically designed for eSeries)	Each
01TA7650	Leak test kit for e-vents	Each

THIS PRODUCT HAS A TWO YEAR WARRANTY AGAINST MANUFACTURERS DEFECTS.



www.otwo.com

45A Armthorpe Road, Brampton, ON, Canada, L6T 5M4
 Telephone: +1 905 792-OTWO (6896) N.A. Toll Free: +1 800 387 3405
 Facsimile: +1 905 799 1339 Email: resuscitation@otwo.com