



pico™ Smokerlyzer®

CO monitoring made easy.


Features and Benefits



Easy to use
touchscreen interface



FREE COdata™
software



Familiar green, amber &
red traffic light system

As easy as...



Hold your breath



Exhale into the device



Instant CO readings

Ideal for in-depth stop smoking advice delivered by:

- Stop smoking services
- General practice
- Schools
- Pharmacies
- Health visitors



Technical Specification

Concentration range	0-150ppm
Display	Full colour touchscreen
Detection principle	Electrochemical sensor
Repeatability	≤±5%
Accuracy	≤±2ppm/5%*
Power	3 x AA (LR6 or equivalent) - up to 1000 minutes 1 x CR2032 Lithium coin cell
T ₉₀ response time	<30 seconds
Operating temperature	15-40°C
Storage/transport temperature	0-50°C
Operating/storage/transport pressure	Atmospheric ±10%
Operating humidity	15-90% RH (non-condensing)
Storage/transport humidity	0-95% RH (non-condensing)
Sensor operating life	5 years
Sensor sensitivity	1ppm
Sensor drift	<5% per annum
Dimensions	Approx. 37 x 77 x 140mm
Weight	Approx. 215g (including batteries)
Materials	Case: polycarbonate/ABS blend Anti-microbial additive D-piece™: Polypropylene SteriBreath™ Eco: Paper OneBreath Mouthpiece: polypropylene
H ₂ cross interference	≤6%

*Whichever is greater

Visit www.bedfont.com/resources to view this document in other languages.



Bedfont® Scientific Ltd.
Station Road, Harrietsham, Maidstone,
Kent, ME17 1JA England
Tel: +44 (0)1622 851122 Fax: +44 (0)1622 854860
Email: ask@bedfont.com Web: www.bedfont.com



Emergo Europe B.V.
Westervoortsedijk 60
6827 AT Arnhem
The Netherlands.

© Bedfont® Scientific Limited 2024

Issue 13 - September 2024, Part No: MKT377
Bedfont® Scientific Limited reserves the right to change or update his literature without prior notice. Registered in: England and Wales. Registered No: 1289798

